

AT800/1200

8/12英寸自动贴膜机

8/12 INCH AUTOMATIC MOUNTER

- **最大有效加工尺寸 (mm)**
Maximum effective product size (mm)

AT800

Ø 8"

AT1200

Ø 12"



● 特点 FEATURE

注: 「*」为选配功能, 支持个性化定制 PS: 「*」 is an optional feature that can be customized by the customer

*可定制自动吸附、自动卸真空功能, 提高效率

* Automatic adsorption and automatic vacuum unload function can be customized improve efficiency.

台面防静电特氟龙处理保护芯片, 可按不同产品定制台面, 台盘更换方便快捷。

Anti-static Teflon treatment of the table top to protect the chip, according to different products Customized table tops, easy and quick to replace the table pan

无气泡快速贴膜。

Bubble-free fast lamination.

设备标配收膜系统。

The equipment comes standard with film collection system.

台盘在不同厚度芯片自适应高度调整, 防产品破碎结构。

Adaptive height adjustment of the table plate in different thickness of chips Anti-product breakage structure.

● 参数 PARAMETER

		AT800		AT1200	
最大工作物尺寸	Max. work object size	Ø8" (向下兼容)	Ø8" (backward compatible)	Ø12" (向下兼容)	Ø12" (backward compatible)
加热温度 (°C)	Heat temperature (°C)	常温 - 160	Normal temperature - 160	常温 - 160	Normal temperature - 160
真空吸附装置	Anti-pinch device	标配	Standard	标配	Standard
电源 (V)	Power supply (V)	两相AC220V±10%	Two-phase AC220V±10%	两相AC220V±10%	Two-phase AC220V±10%
耗电量 (kW)	Power consumption (kW)	0.15		0.15	
压缩空气供给压力 (MPa)	Compressed air supply pressure (MPa)	0.5 - 0.8		0.5 - 0.8	
压缩空气最大消耗量 (L/min ANR)	Max. consumption of compressed air (L/min ANR)	25		25	
设备尺寸 (W x D x H) (mm)	Size (W x D x H) (mm)	450 x 850 x 320		500 x 850 x 320	
设备重量 (kg)	Weight(kg)	≈30		≈40	